



## KDA03

<b>Outside dimension (WxDxH)</b>	760x670x895
<b>Package dimensions (WxDxH)</b>	810x740x1080
<b>Weight (kg)</b>	77
<b>Packaged Weight (kg)</b>	92
<b>Load capacity</b>	3 trays 600x400 or 3 Trays GN 1/1
<b>Trays spacing (mm)</b>	85
<b>Voltage / Frequency</b>	220V - 1~ + N - 50Hz-Γ <sub>II</sub> 230V - 1~ +N - 60Hz-Γ <sub>II</sub>
<b>Cooling capacity*</b>	1125W (50Hz-Γ <sub>II</sub> ) 1316W (60Hz-Γ <sub>II</sub> )
<b>Capacity per cycle</b>	10 kg +90° → +3°C 6 kg +90° → -18°C
<b>Refrigerant Gas</b>	R452a
<b>Max absorbed current</b>	4.9A (50Hz-Γ <sub>II</sub> ) 5.12A (60Hz-Γ <sub>II</sub> )
<b>Max absorbed power</b>	830W (50Hz-Γ <sub>II</sub> ) 972W (60Hz-Γ <sub>II</sub> )
<b>Insulation thickness (mm)</b>	60
<b>Soft &amp; Hard Blast Chilling</b>	◆
<b>Soft &amp; Hard Deep Freezing</b>	◆
<b>Core probe or timed cycle</b>	◆
<b>Storage at the end of each cycle</b>	◆
<b>Automatic defrost</b>	◆
<b>Core probe</b>	-
<b>Options</b>	
<b>Core probe</b>	◇
<b>Hot Gas Defrost</b>	-
<b>HACCP Control</b>	◇
<b>Pivoting Wheels kit</b>	◇
<b>Oven Coupling kit</b>	◇
<b>Sanitisation kit</b>	◇