



KDA05

Outside dimension (WxDxH)	760x670x895
Package dimensions (WxDxH)	810x740x1080
Weight (kg)	82
Packaged Weight (kg)	97
Load capacity	5 trays 600x400 or 5 Trays GN1/1
Trays spacing (mm)	68
Voltage / Frequency	220V - 1~ + N - 50Hz-Γϋ 230V - 1~ +N - 60Hz-Γϋ
Cooling capacity*	1870W (50Hz-Γϋ) 2350W (60Hz-Γϋ)
Capacity per cycle	20 kg +90° → +3°C 13 kg +90° → -18°C
Refrigerant Gas	R452a
Max absorbed current	7A (50Hz-Γϋ) 7A (60Hz-Γϋ)
Max absorbed power	1300W (50Hz-Γϋ) 1500W (60Hz-Γϋ)
Insulation thickness (mm)	60
Soft & Hard Blast Chilling	◆
Soft & Hard Deep Freezing	◆
Core probe or timed cycle	◆
Storage at the end of each cycle	◆
Automatic defrost	◆
Core probe	◆
Options	
Core probe	
Hot Gas Defrost	◇
HACCP Control	◇
Pivoting Wheels kit	◇
Oven Coupling kit	◇
Sanitisation kit	◇