



KDA08

<b>Outside dimension (WxDxH)</b>	790x760x1600
<b>Package dimensions (WxDxH)</b>	830x800x1790
<b>Weight (kg)</b>	128
<b>Packaged Weight (kg)</b>	148
<b>Load capacity</b>	8 trays 600x400 or 8 Trays GN1/1
<b>Trays spacing (mm)</b>	74
<b>Voltage / Frequency</b>	230V - 1~ +N - 50Hz-Г4
<b>Cooling capacity*</b>	3000 W
<b>Capacity per cycle</b>	35 kg +90° → +3°C 20 kg +90° → -18°C
<b>Refrigerant Gas</b>	R452a
<b>Max absorbed current</b>	10.3A
<b>Max absorbed power</b>	2195W
<b>Insulation thickness (mm)</b>	60
<b>Soft &amp; Hard Blast Chilling</b>	◆
<b>Soft &amp; Hard Deep Freezing</b>	◆
<b>Core probe or timed cycle</b>	◆
<b>Storage at the end of each cycle</b>	◆
<b>Automatic defrost</b>	◆
<b>Core probe</b>	◆
<b>Options</b>	
<b>Core probe</b>	
<b>Hot Gas Defrost</b>	◇
<b>HACCP Control</b>	◇
<b>Pivoting Wheels kit</b>	◇
<b>Oven Coupling kit</b>	◇
<b>Sanitisation kit</b>	◇