



KDA15

Outside dimension (WxDxH)	790x760x1950	790x760x1950	790x760x1950
Package dimensions (WxDxH)	830x800x2150	830x800x2150	830x800x2150
Weight (kg)	161	161	162
Packaged Weight (kg)	183	183	184
Load capacity	15 trays 600x400 or 15 Trays GN1/1	15 trays 600x400 or 15 Trays GN1/1	15 trays 600x400 or 15 Trays GN1/1
Trays spacing (mm)	70	70	70
Voltage / Frequency	220V - 3~ - 50Hz-ГЦ 220V - 3~ - 60Hz-ГЦ	400V - 3~ +N - 50Hz-ГЦ	440V - 3~ +N - 60Hz-ГЦ
Cooling capacity*	4771W (50Hz-ГЦ) 5726W (60Hz-ГЦ)	4767W	5230W
Capacity per cycle	60 kg +90° → +3°C 40 kg +90° → -18°C	60 kg +90° → +3°C 40 kg +90° → -18°C	60 kg +90° → +3°C 40 kg +90° → -18°C
Refrigerant Gas	R452a	R452a	R452a
Max absorbed current	11.71(50Hz-ГЦ) 12.96(60Hz-ГЦ)	6.74A	7.12A
Max absorbed power	3657W (50Hz-ГЦ) 4364W (60Hz-ГЦ)	3512W	4060W
Insulation thickness (mm)	60	60	60
Soft & Hard Blast Chilling	◆	◆	◆
Soft & Hard Deep Freezing	◆	◆	◆
Core probe or timed cycle	◆	◆	◆
Storage at the end of each cycle	◆	◆	◆
Automatic defrost	◆	◆	◆
Core probe	◆	◆	◆

Options

Core probe

Hot Gas Defrost	◇	◇	◇
HACCP Control	◇	◇	◇
Pivoting Wheels kit	◇	◇	◇
Oven Coupling kit	◇	◇	◇
Sanitisation kit	◇	◇	◇