



## SQ04M00

<b>CAPACITY, DIMENSIONS, WEIGHT</b>	///
Capacity trays	4 600x400-GN1/1
Distance between trays (mm)	80
Unit size with handle WxDxH (mm)	GRID
Type of rack holder	937 X 885 X 715
Unit size without handle WxDxH (mm)	937 X 821 X 715
Chamber size WxDxH (mm)	660 X 490 X 452
Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1020 X 970 X 868
Unit weight (Kg)	86
Unit weight with packaging (Kg)	102
<b>ELECTRICAL DATA</b>	///
Number of engines	2
Frequency (Hz)	50
Power (kW)	10,5
Voltage	A 400V 3N~
	B NO
	C NO
	D 230V 3~
Current (A)	A 16,5
	B NO
	C NO
	D 28,5

Alimentation cable / plug	A	NO
	B	NO
	C	NO
	D	NO
<b>WATER CONNECTION REQUIREMENTS</b>	///	
Water inlet	YES	
Water drain	YES	
Minimum water quality standards	5° f	
<b>FUNCTIONAL CHARACTERISTICS</b>	///	
Supply	ELECTRIC	
Control panel	MECHANICAL	
Multilingual command	NO	
Cooking type	CONVECTION	
Max cooking temperature (°C)	280	
Cooking chamber material	AISI 304	
Opening door	FROM RIGHT TO LEFT	
Easy clean internal glass	YES	
<b>STANDARD EQUIPMENT</b>	///	
Washing	NO	
Core probe	NO	
<b>VARIANTS</b>	///	
Packaging	WOODEN PALLET CRATE	
Packaging size WxDxH (mm)	1020 X 970 X 873	
Frequency (Hz)	60	
Power (kW)	12,4	
Voltage	A	400V 3N~
	B	NO
	C	NO
	D	230V 3~
Current (A)	A	19,3
	B	NO
	C	NO
	D	33,4
Alimentation cable / plug	A	NO
	B	NO
	C	NO
	D	NO
<b>ACCESSORIES</b>	///	
Self clean system	NO	

Stainless steel tray rack holder	NO
Stainless steel grid rack holder	"5 600x400 80mm 5 GN1/1 80mm"
Oven stand	T9S
	T9S
	T9L
Condensation hood	H10SQ
Water condensation hood	NO
Proofer	CA9308
Overlapping kit for 2 ovens	SK42
Blast chiller	KDA5
Overlapping kit for blast chillere + 1 ovens	SK43
Smoker	SMK02
Core probe	NO
Core probe for vacuum	NO
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adaptor	WPA
Manual shower kit	S1
"Detergent 750ML (for Self clean system or Manual shower kit)"	DT1
"Detergent 6KG (only with self clean system)"	NO
"Detergent 10KG (only with self clean system)"	NO
Wheels kit for stand	R60B
Core probe	-
Core probe for vacuum	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adaptor	WPA
Manual shower kit	S1
"Detergent 750ML (for Self clean system or Manual shower kit)"	DT1
"Detergent 6KG (only with self clean system)"	-
"Detergent 10KG (only with self clean system)"	-

**FEATURES**

◆ Standard | ◇ Optional | - Not available

MANUAL COOKING		
Convection cooking	30°C - 280°C	◆
Mixed steam and convection cooking	30°C - 230°C	◆
Steaming	35°C - 130°C	◆
Dry air cooking	30°C - 280°C	◆
Delta T cooking with core probe		-
With core probe		-
Low temperature cooking		◆
Sous Vide cooking		-
SPECIAL CYCLES		
Multi-level mix:		-
Core probe regeneration		-
Timed regeneration		◆
V-OVERNIGHT COOKING		
V-COOK & HOLD		-
Multi-timer cooking		-
Proofing		-
Automatic Cooling		-
V-SELF CLEANING SYSTEM		
V-RINSING SYSTEM		-
AUTOMATIC COOKING		
V-RECIPE BOOK		-
Program: possibility to memorize program with name and picture		-
Overnight automatic cleaning program		-
Automatic pre-heating setting		-
Programmable timers		-
Cooking cycles for each program		-
AIR DISTRIBUTION IN THE COOKING CHAMBER		
V-BI.DIRETIONAL REVERSING FAN		◆
Number of speed regulation	1	
OVERLAP SYSTEM		
V- OVERLAP CONNECTION with ovens		◇
V- OVERLAP CONNECTION with Venix's Blast Chillers		◇
V- OVERLAP CONNECTION with Venix's Proofing		◇
V- OVERLAP CONNECTION with Venix's Stand		◇

OTHER FUNCTIONS			
Infinity time			◆
Multilangue software			-
Temperature parameter unit F° or C°			◇
Gas reset	LED		◆
V - LIGHTS			◆
Lights integrated in the door			
CONNECTION			
USB			-
WI-FI			-
VENIX-CLOUD			
TECHNICAL DETAILS			
Internal glass easy clean system			◆
V- BREAK DROP technology for excellent humidity			◆
Thermal insulation structure (energetic efficiency)			-
Inverter technology			-
External connection for 2nd core probe			◆
Digital water injection regulation			◆



## SQ04MV0

2 Speed regulation

<b>CAPACITY, DIMENSIONS, WEIGHT</b>	///	
Capacity trays	4 600x400-GN1/1	
Distance between trays (mm)	80	
Unit size with handle WxDxH (mm)	GRID	
Type of rack holder		
Unit size without handle WxDxH (mm)	937 X 821 X 715	
Chamber size WxDxH (mm)	660 X 490 X 452	
Packaging	PALLET + CARTON BOX	
Packaging size WxDxH (mm)	1020 X 970 X 868	
Unit weight (Kg)	86	
Unit weight with packaging (Kg)	102	
<b>ELECTRICAL DATA</b>	///	
	Number of engines	2
	Frequency (Hz)	50
	Power (kW)	10,5
	Voltage A	400V 3N~
	B	NO
	C	NO
	D	230V 3~
	Current (A) A	16,5
	B	NO
	C	NO
	D	28,5

Alimentation cable / plug	A	NO
	B	NO
	C	NO
	D	NO
<b>WATER CONNECTION REQUIREMENTS</b>	///	
Water inlet	YES	
Water drain	YES	
Minimum water quality standards	5° f	
<b>FUNCTIONAL CHARACTERISTICS</b>	///	
Supply	ELECTRIC	
Control panel	MECHANICAL 2 SPEED	
Multilingual command	NO	
Cooking type	CONVECTION	
Max cooking temperature (°C)	280	
Cooking chamber material	AISI 304	
Opening door	FROM RIGHT TO LEFT	
Easy clean internal glass	YES	
<b>STANDARD EQUIPMENT</b>	///	
Washing	NO	
Core probe	NO	
<b>VARIANTS</b>	///	
Packaging	WOODEN PALLET CRATE	
Packaging size WxDxH (mm)	1020 X 970 X 873	
Frequency (Hz)	60	
Power (kW)	12,4	
Voltage	A	400V 3N~
	B	NO
	C	NO
	D	230V 3~
Current (A)	A	19,3
	B	NO
	C	NO
	D	33,4
Alimentation cable / plug	A	NO
	B	NO
	C	NO
	D	NO
<b>ACCESSORIES</b>	///	
Self clean system	NO	

Stainless steel tray rack holder	NO
Stainless steel grid rack holder	"5 600x400 80mm 5 GN1/1 80mm"
Oven stand	T9S
	T9S
	T9L
Condensation hood	H10SQ
Water condensation hood	NO
Proofer	CA9308
Overlapping kit for 2 ovens	SK42
Blast chiller	KDA5
Overlapping kit for blast chillere + 1 ovens	SK43
Smoker	SMK02
Core probe	NO
Core probe for vacuum	NO
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adaptor	WPA
Manual shower kit	S1
"Detergent 750ML (for Self clean system or Manual shower kit)"	DT1
"Detergent 6KG (only with self clean system)"	NO
"Detergent 10KG (only with self clean system)"	NO
Wheels kit for stand	R60B
Core probe	-
Core probe for vacuum	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adaptor	WPA
Manual shower kit	S1
"Detergent 750ML (for Self clean system or Manual shower kit)"	DT1
"Detergent 6KG (only with self clean system)"	-
"Detergent 10KG (only with self clean system)"	-



**FEATURES**

◆ Standard | ◇ Optional | - Not available

**MANUAL COOKING**

Convection cooking	30°C - 280°C	◆
Mixed steam and convection cooking	30°C - 230°C	◆
Steaming	35°C - 130°C	◆
Dry air cooking	30°C - 280°C	◆
Delta T cooking with core probe		-
With core probe		-
Low temperature cooking		◆
Sous Vide cooking		-

**SPECIAL CYCLES**

Multi-level mix:		-
Core probe regeneration		-
Timed regeneration		◆
<b>V-OVERNIGHT COOKING</b>		-
<b>V-COOK &amp; HOLD</b>		-
Multi-timer cooking		-
Proofing		-
Automatic Cooling		-
<b>V-SELF CLEANING SYSTEM</b>		-
<b>V-RINSING SYSTEM</b>		-

**AUTOMATIC COOKING**

<b>V-RECIPE BOOK</b>		-
Program: possibility to memorize program with name and picture		-
Overnight automatic cleaning program		-
Automatic pre-heating setting		-
Programmable timers		-
Cooking cycles for each program		-

**AIR DISTRIBUTION IN THE COOKING CHAMBER**

<b>V-BI.DIRETIONAL REVERSING FAN</b>		◆
Number of speed regulation	2	

**OVERLAP SYSTEM**

<b>V- OVERLAP CONNECTION with ovens</b>		◇
<b>V- OVERLAP CONNECTION with Venix's Blast Chillers</b>		◇
<b>V- OVERLAP CONNECTION with Venix's Proofing</b>		◇
<b>V- OVERLAP CONNECTION with Venix's Stand</b>		◇

OTHER FUNCTIONS			
Infinity time			◆
Multilangue software			-
Temperature parameter unit F° or C°			◇
Gas reset	LED		◆
V - LIGHTS			◆
Lights integrated in the door			
CONNECTION			
USB			-
WI-FI			-
VENIX-CLOUD			
TECHNICAL DETAILS			
Internal glass easy clean system			◆
V- BREAK DROP technology for excellent humidity			◆
Thermal insulation structure (energetic efficiency)			-
Inverter technology			-
External connection for 2nd core probe			◆
Digital water injection regulation			◆